



SDI streaming node

SDI streaming node



NDI HX2 Stabilize

H.264 Coding Low Bandwidth

Multi-input HDMI、SDI、UVC

Support Input Source Preview

Tally Feedback PTZ Status

UVC Control PTZ Adjust focus and angle remotely

NDI[®] Codec Function

NDI HX2 H.264 Encoding, low bandwidth,
stable, high quality.



Low Loss

Low Latency

More
Stable



NDI®

CAT 6



TAO 1 pro-S

HDMI



Monitor

can be decoded
able to encode



Monitor

HDMI



TAO 1 pro-S

CAT 6



Live Platform



USB UVC



HDMI



SDI

Multi-input HDMI, SDI, UVC

More port options, SDI port makes the equipment more professional.



Support Input Source Preview

Switch preview function, support preview signal source function, no need to worry about switching errors when switching between multiple signal sources.



Tally Light Control

Tally and PTZ will always feed back device information.



Multi-mode PTZ control

UVC controls PTZ, which can remotely adjust the focal length and angle of the camera, and can easily control the camera without logging in to the background management interface.



Specification

Connectors					
Input	HDMI 1.3	1×HDMI-A	Audio	In	1×3.5mm Audio Jack
	SDI	1×BNC		Out	1×3.5mm Audio Jack
	USB 3.0	2×USB-A	Communication	LAN	1×RJ45
Output	HDMI 2.0	1×HDMI-A		Power	1×USB-C
Output	USB 2.0	2×USB-A			

Performance					
Input	HDMI				
Resolutions	SMPTE	720p@50/60 1080p@23/24/60			
	VESA	1024×768@60 1280×720@60 1280×800@60 1280×1024@60 1360×768@60 1600×1200@60 1680×1050@60 1920×1080@60			
Output	HDMI				
Resolutions	SMPTE	720p@50/60 1080p@24/25/50/60 2160p@60			
	VESA	1024×768@60 1280×720@50/60 1280×800@60 1280×1024@60 1360×768@60 1920×1080@50/60 3840×2160@60			

Screen Feature					
Screen Dimension	5.5" TFT		Brightness	450cd/m²	
Resolution	1080×1920 pixels		Contrast	1000:1	
Dot Pitch	0.063(H)×0.021(W)(mm)		Backlight	LED	
Aspect Ratio	16:9		View Angle	80°/80°(L/R)/80°/80°(U/D)	

Power					
Input Voltage	9V/2A		Max Power	18W	

Environment					
Temperature	0°C~55°C		Humidity	5%~85%	

Physical					
Weight	Net	350g(without battery) 882g(with battery)	Package	770g	
Dimension	Net	161mm×106mm×36mm	Package	255mm×145mm×85mm	



WEB: www.rgblink.com EMAIL: taotiny@rgblink.com PHONE: +19033001197