


# ACM-582

## Array Ceiling Microphone



### Description

Relacart latest innovation, the ACM-582 AI Ceiling Microphone Array, combines cutting-edge AI technology and advanced acoustic engineering to deliver unparalleled audio quality for any space. This ceiling-mounted solution is not just a technological breakthrough but a versatile tool for environments like conference rooms, classrooms, and auditoriums, ensuring every word is captured with precision and clarity.

### Product Specification

Coverage Area :	25×25 ft (7.6×7.6 m)
Coverage Type :	Automatic
Power Requirements:	PoE/PoE+ (IEEE 802.3af/at)
Power Consumption:	Max 3W
Control Software:	TDM
Cable Requirement:	Cat5e or higher (shielded recommended)
Connector Type:	RJ45
Plenum Rating :	UL2043 (suitable for air-handling spaces)
Dust Protection:	IEC 60529 IP5X
Operating Temperature:	-5°C (23°F) to 40°C (104°F)
Storage Temperature :	-25°C (-13°F) to 60°C (140°F)
Microphone Element:	5 MEMS arrays
Frequency Response :	100Hz – 8kHz
AES67/Dante Output – Channels :	1 channel
AES67/Dante Output – Sample Rate:	48kHz
AES67/Dante Output – Bit Depth :	24-bit
Sensitivity (at 1kHz) :	-1.5dBFS/Pa
Max SPL :	96dB SPL
SNR (ref. 94dB SPL, 1kHz) :	75dB (A-weighted)
Latency (excl. Dante latency):	48ms
Self-Noise:	22dB SPL (A-weighted)
Dynamic Range :	75dB
Process :	Acoustic Echo Cancellation (AEC), AI Noise Reduction, Auto Gain Control (AGC), Mute Function
Dimensions :	582*582*51.9(mm)